



SHEAR&BALER ELLE



LOADING -UNLOADING

The "ELLE" loading and unloading shears&balers are suitable for users who need to move frequently or rent them to third parties.

They work simply resting on the ground and they are easly to position and start up.

The shear&balers of this group can produce bales that are automatically ejected.

The "ELLE" transportable shears&balers are equipped with 4 lifting cylinders to allow loading and unloading from the transport vehicle, the maximum lifting height is 1100 mm.

The supporting structure is fitted with 2 additional rear cylinders to ensure stability and alignment to the ground.

The "ELLE" line is equipped with the original TAURUS "swinging wing" compression system with ovestroke on both wings SBxc (patented).





Clamp

Indicative weight

SHEAR&BALER ELLE

ELLE L662 L762 L873 L973 Cutting force 600 700 800 900 tons ۲ ٠ ۲ ٠ 900x600 900x600 900x600 900x600 **Bale dimension** mm Open box width mm 2800 2800 2800 2800 Box length mm 6100 6100 7200 7200 2 2 3 3 Cylinder per wing n. Max. compression force (each wing) 300 300 450 450 tons Main cylinder compression force tons 150 150 150 150 **Diesel engine** hp 280 280 400 400

80

85

100

4+2



tons



TAURUS Via Cesare Battisti, 77 21020 Daverio (VA-IT)



T. +39 0332947242 info@taurusweb.it www.taurusweb.it

105