



SHEAR&BALER RAPID S



TECHNOLOGY AND EXPERIENCE

A concentration of technology and experience, strength and speed, robustness and simplicity of construction, reliability and safety. "RAPID" shears&balers are synonymous with production, low consumption, high performance. "RAPID" shears&balers are designed for heavy duty work, for those who demand quality, clean and high density scrap metal. Machines adapt to HEAVY-DUTY, suitable to shear particular consistency scrap (demolition, production scraps, stamping and rolling trimmings, pantographed sheet metal scraps, reinforced concrete rod, rails...).

"RAPID" comes in two different configurations, "H" and "S" type.

The "S" type supported by two indipendent frames integrated and connected; one part supporting the shear and the compression box, the other part the engines and the hydraulic system. The machine includes a cover in tubular structure to protect the shear head and covers to protect the cylinders of the lids. The hydraulic system is covered and protected by a platform mounted longitudinally to the machine above the feeding cylinder, complete with cabin, ladder and handrails. "RAPID" does not need foundations. They are the evolution of the well-established and tested "swinging wing" compression system.





SHEAR&BALER RAPID S

RAPID		R s117	R s127	R s137
Cutting force	tons	1100	1200	1300
Clamp	tons	280	280	280
Bale dimensions	mm	1000x700	1000x700	1000x700
Open box width	mm	2900	2900	2900
Box length	mm	7200	7200	7200
Cylinders per wing	n	3	3	3
Max. compression force (each wing)	tons	450	450	450
Main cylinder compression force	tons	150	150	150
Main electric power	kw	2x200	2x200	2x200
Diesel engine	hp	560	560	560
Indicative weight	tons	190	210	210



